

# Material Safety Data Sheet

## AccuLac<sup>®</sup> 1400



### SECTION 1 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: AccuLac 1400  
Item Number: 5001400  
Product Use: Water-based Liquid Coating  
Date: 11/28/2007

Supplier: Neschen Americas  
7091 Troy Hill Drive  
Elkridge, MD 21075

Emergency Telephone: 800-486-6502 8:00am – 5:00pm  
After Hour MSDS Available at: [www.neschenbrands.com/MSDS](http://www.neschenbrands.com/MSDS)

### SECTION 2 – COMPOSITION/INFORMATION ON INGREDIENTS

Item	Chemical Name	OSHA PEL	ACOH TLV	Other Limits	Wt. %
01	N-Methyl Pyrrolidone	Not Established	Not Established	Not Established	6-9%
02	GlycolEther (CAS 34590-94-8)	100ppm	25ppm	Not Established	1-4%
03	N,N Diethylethanamine	10ppm	10ppm	Not Established	0-3%
04	Bis (1,2,2,6,6-Pentamethyl – 4 – piperidinyl) sebacate	Not Established	Not Established	Not Established	>1%
05	Methyl (1,2,2,6,6 – Pentamethyl – N/E 4 – piperidinyl)sebacate	Not Established	Not Established	Not Established	>1%
06	3-(2H-Benzotriazol-2-yl)-5- (1,1-dimithylethyl)-4 – hydroxybenzene propamoic acid, C7-9-branchedalkylesters	Not Established	Not Established	Not Established	0-5%

### SECTION 3 – PHYSICAL AND CHEMICAL PROPERTIES

Boiling Range:	190 - 396°F	Vapor Density:	Is heavier than air
Odor:	Low	Odor Threshold:	Not Determined
Appearance:	White colored liquid	Evaporation Rate:	Is slower than Butyl Acetate
Solubility in H <sub>2</sub> O:	100%	Specific Gravity:	Not Determined
Freeze Point:	Not Determined	pH @ 0.0%:	8.4
Vapor Pressure:	Not Determined	Viscosity:	Not Determined
Physical State:	Not Determined	Density:	8.2 lbs/gal
Weight % Solids:	100.00	Melting Point:	32°F
% VOC	8-10%		

### SECTION 4 – FIRE AND EXPLOSION HAZARD DATA

**Flash Point:** 200°F

**Lower Explosive Limit:** Not Established

**Upper Explosive Limit:** Not Established

**Autoignition Temperature:** Not Established

**Extinguishing Media:** Foam, dry chemical, carbon dioxide

**Unusual Fire and Explosion Hazards:** None

**Special Firefighting Procedures:** As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Remove all ignition sources.

# Material Safety Data Sheet

## AccuLac<sup>®</sup> 1400



---

### SECTION 5 – STABILITY AND REACTIVITY

**Conditions to Avoid:** Storage above 100°F (37.8°C), exposure to light and excessive heat.

**Incompatibility:** Peroxides, strong oxidizing agents, copper, copper alloys, iron, iron oxides and alloys, strong bases.

**Hazardous Decomposition Products:** Burning may produce carbon dioxide and carbon monoxide.

**Hazardous Polymerization:** Could occur under normal conditions.

**Stability:** This product is stable under normal storage conditions.

---

### SECTION 6 – ACCIDENTAL RELEASE MEASURES

**Steps to be taken in case material is release or spilled:** Absorb spill with inert materials then place in a chemical waster container. Avoid runoff into storm sewers and ditches which lead to waterways. Spontaneous polymerization may occur. Eliminate ignition sources. Use eye and skin protection. Ventilate area.

**Spill or Leak Procedures:** Eliminate sources of ignition. Wear necessary protective clothing. Place leaking containers in well ventilated area. Absorb spills with inert materials such as vermiculite or sand. Dispose according to federal, state and local regulations. Do not flush to waterways. Spills may be reportable to the National Response Center (1-800-424-8802).

**Engineering Controls:** Use adequate ventilation. Local exhaust is recommended to control exposure when operations generate aerosol or vapors.

**Disposal Methods:** Dispose in accordance with federal, state and local regulations.

**Storage Method:** Store in properly sealed container. Avoid temperature below freezing. Avoid temperatures above 100° F (38°C)

---

### SECTION 7 – HAZARDS IDENTIFICATION

**Emergency Overview** – May cause skin irritation. May be irritating to eyes. Vapor from heated product may cause eye and respiratory irritation.

**Effects of Overexposure – Eye Contact:** Can cause eye irritation, redness, tearing. May cause eye irritation or injury which may persist for days.

**Effects of Overexposure – Skin Contact:** May cause skin irritation. Allergic reactions are possible. May cause skin sensitization, allergic reaction, which becomes evident on re-exposure to this material. Burns can result from prolonged contact.

**Effects of Overexposure – Inhalation:** Excessive inhalation of vapors can cause nasal and respiratory irritation, and central nervous system effects such as dizziness, fatigue, nausea, headache. If product is sprayed, inhalation of solid airborne particles may irritate the respiratory tract and lungs.

**Effects of Overexposure – Ingestion:** No hazard in normal industrial use.

**Effects of Overexposure – Chronic Hazards:** No chronic effects expected in normal use. Limited evidence of mutagenicity.

**Primary Route(s) of Entry:** SKIN CONTACT INHALATION EYE CONTACT.

---

# Material Safety Data Sheet

## AccuLac<sup>®</sup> 1400



---

### SECTION 8 – FIRST AID MEASURES

**First Aid – Eye Contact:** Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation persists.

**First Aid – Skin Contact:** Wash with soap and water. Get medical attention if irritation develops or persists. Wash contaminated clothing before reuse. Immediately remove clothing and wash affected area with soap and water for at least 15 minutes. Material is difficult to remove. Do not use solvent to clean skin as this increases penetration. Incinerate leather shoes, belts, etc., as these cannot be cleaned. Wash clothing thoroughly before reuse.

**First Aid – Inhalation:** Remove from exposure, treat symptomatically. Get medical attention if symptoms persist.

**First Aid – Ingestion:** Get medical attention immediately. If swallowed, give water to dilute. Do not induce vomiting. If swallowed in appreciable amounts, get medical attention. Very small amounts are practically non-toxic.

---

### SECTION 9 – PRECAUTIONS FOR SAFE HANDLING AND USE

**Handling:** Wash thoroughly after handling. Use with adequate ventilation. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Do not store above 100°F. Dissolved air is required for inhibitor to function. To prevent loss of inhibitor, do not blanket with nitrogen. Store in opaque or amber glass containers. Material may solidify at low temperatures, and may be melted in a water bath no warmer than 120°F for no more than 24 hours. Never use steam or electrical heaters.

**Storage:** Keep away from heat, sparks, and flame. Keep container closed when not in use. This product is inhibited to prevent uncontrolled polymerization. Polymerization can generate heat and pressure and may cause product container to rupture. Check inhibitor space often and add inhibitor to bulk liquid if needed. Maintain head space in storage containers to support oxygen requirements of the inhibitor(s). Prevent materials from freezing (inhibitor can separate from product as a solid). Store below 90°F (32°C) and away from heat sources, strong oxidizers, radiation and other initiators. Use product within six months. Do not heat material with a drum heater.

**Disposal Method:** Not considered a hazardous waste by RCRA regulations. Incinerate or use biological treatment in accordance with federal, state, and local regulations. Do not incinerate in a closed container. Incineration is recommended.

---

### SECTION 10 – CONTROL MEASURES

**Ventilation:** Adequate ventilation is required when handling this product. Local exhaust is recommended to vent aerosol or vapors.

**Respiratory Protection:** When exposed to significant amounts of aerosols or vapors, use full face respirator with organic vapor cartridge and particulate pre-filter. Use self contained breathing apparatus (SCBA) in confined spaces (29 CFR 1910.146) or emergency situations.

**Skin Protection:** Wear chemically impervious gloves. Use a face shield, impervious apron or outerwear and boots during operations where significant contact can occur.

**Eye Protection:** Avoid contact with eyes. Wear chemical splash goggles or safety glasses.

**Other Protective Equipment:** Where splashing is possible, an impermeable apron and boots should be worn. Neoprene gloves are recommended. For operations where contact can occur, a face shield, impervious body covering and boots are recommended.

**Hygienic Practices:** Avoid long and repeated contact with skin. Safety shower and eye wash facility should be available.

---

# Material Safety Data Sheet

## AccuLac® 1400



### SECTION 11 – REGULATORY INFORMATION

**Status on Substance Lists:** The concentrations shown are maximum or ceiling levels (weight %) to be used for calculations for regulations. Trade Secrets are indicated by "TS"

**TSCA :** All components of this material are included on the TSCA inventory of chemical substances.

N-methyl pyrrolidone is the subject of an enforceable consent agreement concerning health effects testing under TSCA section 4(a) (40 CFR 799.5000). As a result, any export of this product is subject to TSCA section 12(b) notification requirements (40 CFR 707.60) reports to US EPA should reference N-methyl pyrrolidone (CAS # 872-50-4).

Comprehensive Environmental Response Compensation, and Liability Act of 1980 (CERCLA) requires notification of the National Response Center of release of quantities of Hazardous Substance equal to or greater than the reportable quantities (RQs) in 40 CFR 302.4.

Components present in this product at a level which could require reporting under the statute are: NONE

Superfund Amendments and Reauthorization Act of 1988 (SARA) Title III requires emergency planning based on Threshold Planning Quantities (TPQs) and release reporting based on Reportable Quantities (RQs) in 40 CFR 355 (used for SARA 302, 311, and 312).

Components present in this product at a level which could require reporting under the statute are: NONE

Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires submission of annual reports of release of toxic chemicals that appear in 40CFR 372 (for SARA 313). This information must be included in all MSDS that are copied and distributed for this material.

Components present in this product at a level which could require reporting under the status are: NONE

**TSCA INVENTORY STATUS:** All components of this product are listed on the TSCA registry

### SECTION 12 - STATE RIGHT-TO-KNOW

**CALIFORNIA Proposition 65.** Components present in this product at a level which could require reporting under the statute are: NONE

**MASSACHUSETTS 105 CMR 670,000 Right-to-Know.** Substance List (MSL) Hazardous Substances and Extraordinary Hazardous Substances on the MSL must be Identified when present in products. Components present in this product at a level which could require reporting under the statute are: NONE

**PENNSYLVANIA and/or NEW JERSEY Right-to-Know.** Hazardous Substance List Hazardous Substances and Special Hazardous Substances on the List must be identified when present in products.

Components present in this product at a level which could require reporting under the statute are: N-methyl pyrrolidone (CAS # 872-50-4)

**OTHER REGULATORY INFORMATION:** NONE KNOWN

Neschen Americas expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose, with respect to the product or information provided herein. All information appearing herein is based upon data obtained from the manufacturer and /or recognized technical sources. While the information is believed to be accurate, Neschen Americas makes no representations as to its accuracy of sufficiency. Conditions of use are beyond Neschen Americas control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling and disposal of the product, or from the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

----- THE END -----