

# Printex™ Easy Banner Light

## Product Specifications



Material Details	
Material	100% Polyester
Weight	4.9 oz/yd <sup>2</sup> (165 g/m <sup>2</sup> )
Thickness	7.5 mil
Brightness (L*)	91.55
Breaking resistance (lbs/in)	md: >110    cmd: >57
Elongation at break (%)	md: >20    cmd: >20
Tensile Strength (lbs/in)	md: 137    cmd: 96
Tear resistance (lbs)	md: 24    cmd: 17
Handling/Storage Conditions	10° to 25°C / 50° to 77°F at 20-60% relative humidity
Shelf Life	1 year after the production date
Fire protection	B1 test certificate according to DIN 4102-1

### Areas of Application

- Roll Up display systems
- Tradeshow graphics
- Point of purchase graphics
- Suitable for indoor and short term outdoor (printed with pigmented inks) applications

### Advantages / Special Features

- Good stiffness (no edge curl)
- Can be used in backlit applications
- High resolution capable
- Fast drying
- Part of Neschen's INDISPLAY solutions

### Process & Handling

- To avoid fingerprints, it is recommended that protective gloves be worn while handling.
- To prevent problems after printing, make sure all prints have been allowed sufficient time to thoroughly dry (dry time of 12 hours to be assured).

Printability	
Aqueous dye inks	◆
Aqueous pigment inks	◆



Temperatures and thicknesses are given as approximate values. All data are standard values. The information in this specification sheet is based on findings obtained in practice. Because of the high number of factors which can have an effect during handling and application, customer tests will be required. A legally binding guarantee of specific properties is not to be inferred from our specifications. The information given here may be subject to change without notice. Neschen has not prepared MSDSs for these products which are not subject to the MSDS requirements of the Occupational Safety and Health Administration's Hazard Communication Standard, 29 C.F.R. 1910.1200(b)(6)(v). When used under reasonable conditions or in accordance with the Neschen directions for use, these products should not present a health and safety hazard. However, use or processing of the products in a manner not in accordance with the directions for use may affect their performance and present potential health and safety hazards. The purchaser should test material to determine if it is suitable for their own specific purpose.