

SolvoPrint™ Easy Panel 220

Product Specifications



Material Details		
Carrier Material	Rigid PVC	
Thickness	220 µm	8.66 mil
Weight	310 g/m ²	9.14 oz/yd ²
Gloss Level	Satin coating	
Opacity	>98%	
Brightness	91.20	
Whiteness	95.5 W(CIE)	
Storage Conditions	Store boxed at 10 - 35°C / 50 - 95°F, 20-70% relative humidity	
Shelf Life	2 years	
Temperature Resistance	Shrinkage: long = max. -8% transversal = max +/- 2%	

Areas of Application

- Roll Up and Pop Up display systems
- Trade show and exhibit graphics
- Retail and promotional signage
- Outdoor signage and advertising
- Suitable for indoor and for short term outdoor application use

Advantages / Special Features

- Good stiffness (no edge curl)
- Soft satin finish
- Opaque appearance
- Very good color reproduction and photorealistic print quality
- Fast drying
- Part of Neschen's INDISPLAY solutions

Process & Handling

- Heaters should be set to a maximum of 95°F (35°C) to avoid scalloping
- To avoid finger prints, usage of cotton gloves is recommended
- For protective purpose usage of Neschen Protective Laminates is recommended (ensure adequate drying before lamination) – drying time of min. 12 hours is recommended
- Store unused media in the original packaging

Recommended Protection Films

- Print Shield® Floor Guard



Printability	
Solvent	◆
Eco Solvent	◆

Temperatures and thicknesses are given as approximate values. All data are standard values. The information in this specification sheet is based on findings obtained in practice. Because of the high number of factors which can have an effect during handling and application, customer tests will be required. A legally binding guarantee of specific properties is not to be inferred from our specifications. The information given here may be subject to change without notice. Neschen has not prepared MSDSs for these products which are not subject to the MSDS requirements of the Occupational Safety and Health Administration's Hazard Communication Standard, 29 C.F.R. 1910.1200(b)(6)(v). When used under reasonable conditions or in accordance with the Neschen directions for use, these products should not present a health and safety hazard. However, use or processing of the products in a manner not in accordance with the directions for use may affect their performance and present potential health and safety hazards. The purchaser should test material to determine if it is suitable for their own specific purpose.